


303.5E CR, 304E CR, 305E CR, 305.5E CR Specifications

305E CR Dimensions



	Standard Stick		Long Stick	
1	3280 mm	10'9"	3670 mm	12'1"
2	2320 mm	7'7"	2630 mm	8'8"
3	5430 mm	17'10"	5810 mm	19'1"
4	5600 mm	18'5"	5960 mm	19'7"
5	5250 mm	17'3"	5440 mm	17'10"
6	3720 mm	12'2"	3920 mm	12'10"
7	2350 mm	7'8"	2530 mm	8'3"
8	1100 mm	3'7"	1100 mm	3'7"
9	405 mm	1'4"	405 mm	1'4"
10	555 mm	1'10"	555 mm	1'10"

	Standard Stick		Long Stick	
11	1750 mm	5'9"	2150 mm	7'0"
12	2550 mm	8'4"	2550 mm	8'4"
13	615 mm	2'0"	615 mm	2'0"
14	2580 mm	8'5"	2580 mm	8'5"
15	5180 mm	17'0"	5290 mm	17'4"
16	785 mm	2'7"	785 mm	2'7"
17	695 mm	2'3"	695 mm	2'3"
18	400 mm	1'4"	400 mm	1'4"
19	1980 mm	6'6"	1980 mm	6'6"

305E CR Lift Capacities at Ground Level*

Lift Point Radius		3000 mm (9'8")		4500 mm (14'9")	
		Front	Side	Front	Side
Blade Down	kg	2340	1200	1260	640
	lb	5,159	2,646	2,778	1,411
Blade Up	kg	1450	1070	760	570
	lb	3,197	2,359	1,676	1,257

* The above loads are in compliance with hydraulic excavator lift capacity rating standard ISO 10567:2007 and they do not exceed 87% of hydraulic lifting capacity or 75% of tipping capacity. The excavator bucket weight is not included on this chart. Lifting capacities are for standard stick.