

# RTV

## KUBOTA 4WD DIESEL UTILITY VEHICLE *RTV-X900/RTV-X1110*

For Earth, For Life  
Kubota

Two versatile RTVs, the RTV-X900 and the new more powerful RTV-X1110, offer the power, acceleration, and hill-climbing ability you need for all types of jobs, with your choice of Kubota Orange or Realtree Camo styling.



# SPECIFICATIONS

| Model                            |  | RTV-X900 Non-homologation model         |  | RTV-X1110 Homologation model   |  |
|----------------------------------|--|---|--|--|--|
| Available body colours           |  | Kubota Orange                           |  | Realtree® AP Camo  |  |
| Make                             |  | KUBOTA D902-E-UV                        |  | KUBOTA D1105-E4-UV-2E  |  |
| Type                             |  | 3-cylinders, 4-cycle, diesel, OHV       |  | 3-cylinders, 4-cycle, diesel, OHV  |  |
| Displacement cc                  |  | 898                                     |  | 1123   |  |
| Net Power ECE-R24 kW (PS)        |  | 15.4 (21.0)                             |  | 17.8 (24.2)  |  |
| Cooling system                   |  | Liquid                                  |  | Liquid   |  |
| Battery A                        |  | CCA: 540                                |  | CCA: 650   |  |
| Transmission                     |  | Variable Hydraulic Transmission (VHT-X) |  | Variable Hydraulic Transmission (VHT-X)                                      |  |
| Gear selection                   |  | Hi-Lo range forward, neutral, reverse   |  | Hi-Lo range forward, neutral, reverse  |  |
| Max. travelling speed mph (km/h) |  | 0 – 25 (0 – 40)                         |  | 0 – 25 (0 – 40)  |  |
| 4WD system                       |  | Front differential                      |  | Limited-slip differential  |  |
|                                  |  | Rear differential                       |  | Foot operated differential lock  |  |
| Steering                         |  | Hydrostatic power                       |  | Hydrostatic power  |  |
| Brakes                           |  | Front / Rear                            |  | Wet-disc brakes  |  |
|                                  |  | Parking brake                           |  | Rear wheel, hand operated  |  |
| Suspension                       |  | Front suspension                        |  | Independent, Dual A-arms with coil over shock with adjustable spring preload |  |
|                                  |  | Front suspension travel                 |  | 205  |  |
|                                  |  | Rear suspension                         |  | Independent, Dual A-arms with coil over shock with adjustable spring preload |  |
|                                  |  | Rear suspension travel                  |  | 205  |  |
| Ground clearance                 |  | Front ROPS / CABIN mm (inch)            |  | 265 (10.4) / 252 (9.9)   |  |
|                                  |  | Rear ROPS / CABIN mm (inch)             |  | 259 (10.2) / 257 (10.1)  |  |
| Headlights                       |  | Two, 37.5 watt halogen                  |  | Two, 37.5 watt halogen   |  |
| Occupant Protective System       |  | Seat belts                              |  | 2-point  |  |
|                                  |  | Certification ROPS / CABIN              |  | e12*1322/2014*2016/1788U3*00007 / e12*1322/2014*2016/1788V*00008             |  |
| Dimensions                       |  | Length mm (inch)                        |  | 3130 (123.2)   |  |
|                                  |  | Width ROPS / CABIN mm (inch)            |  | 1605 (63.2)  |  |
|                                  |  | Height, overall mm (inch)               |  | 1990 (78.3)  |  |
|                                  |  | Front tread centers mm (inch)           |  | 1240 (48.8)  |  |
|                                  |  | Rear tread centers mm (inch)            |  | 1240 (48.8)  |  |
|                                  |  | Wheelbase mm (inch)                     |  | 2045 (80.5)  |  |
|                                  |  | Turning radius m                        |  | 4.0  |  |
| Weight (Gross)                   |  | ROPS / CABIN kg                         |  | 960 / 1050   |  |
| Towing capacity                  |  | Unbraked / Inertial-braked kg           |  | 450 on flat ground / 1000 on flat ground                                     |  |
| Payload capacity                 |  | ROPS / CABIN kg                         |  | 585 / 495  |  |
| Cargo bed                        |  | Material                                |  | Steel  |  |
|                                  |  | Width x Length x Depth mm (inch)        |  | 1465 (57.7) x 1030 (40.6) x 285 (11.2)                                       |  |
|                                  |  | Volume m³                               |  | 0.43   |  |
|                                  |  | Bed height (unloaded) mm                |  | 887  |  |
|                                  |  | Cargo bed load kg                       |  | 500  |  |
|                                  |  | Dumping system                          |  | Hydraulic power lift   |  |
| Fuel tank capacity               |  | ℓ                                       |  | 30   |  |
| Tyres (front and rear)           |  | ATV                                     |  | Not available  |  |
|                                  |  | HDWS                                    |  | 25x10-12, 6-ply  |  |
| Front guard design               |  | Center and bumper                       |  | Center and bumper  |  |
| Alloy wheel                      |  | Option                                  |  | Option   |  |
| Hydraulic bed lift               |  | Standard                                |  | Standard   |  |

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty and safety information.

The values in "Ground clearance" and "Weight" are those with the machine equipped with the tyres in the table above. Some RTVs in this brochure are shown with optional accessories. For off-highway use only.